

FAG

## ★ 2206-TVH



Self-aligning ball bearing

Schaeffler ID:  
0167027940000

Self-aligning ball bearing 22...-TVH, plastic cage

★ Preferred product

## Technical information



## Main Dimensions &amp; Performance Data

d	30 mm	Bore diameter
D	62 mm	Outside diameter
B	20 mm	Width
$r_{\min}$	1 mm	Minimum chamfer dimension
$C_r$	26.000 N	Basic dynamic load rating, radial
$C_{0r}$	6.900 N	Basic static load rating, radial
$C_{ur}$	440 N	Fatigue load limit, radial
$n_G$	11.500 1/min	Limiting speed
$n_{gr}$	11.400 1/min	Reference speed
	0,003 kg	Weight

## Dimensions

$D_1$	53,7 mm	Shoulder diameter outer ring
$d_1$	38,5 mm	Shoulder diameter inner ring

## Mounting dimensions

$d_{a\min}$	35,6 mm	Minimum diameter shaft shoulder
$D_{a\max}$	56,4 mm	Maximum diameter of housing shoulder
$r_{a\max}$	1 mm	Maximum fillet radius

## Calculation factors

e	0,31	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	2,01	Dynamic axial load factor
$Y_2$	3,11	Dynamic axial load factor
$Y_0$	2,11	Static axial load factor

## Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.