



## ★ GE12-UK


### Spherical plain bearing

Schaeffler ID:  
0066497690000

★ Preferred product

Radial spherical plain bearing, maintenance-free, sliding layer: PTFE composite, inner ring curved surface with hard chromium coating, DIN ISO 12240-1, dimension series E, open design


### Technical information



### Main Dimensions & Performance Data

D	22 mm	Outside diameter bearing
d	12 mm	Bore diameter bearing
B	10 mm	Width Inner ring
C	7 mm	Width Outer ring
$C_r$	11.300 N	Basic dynamic load rating, radial
$C_{0r}$	28.400 N	Basic static load rating, radial
	15,66 g	Weight

### Dimensions



$d_k$	18 mm	Ball diameter
$\alpha$	11 °	Tilt angle
$G_r$	0 - 0,032 mm	Radial Clearance
$d_{OT}$	0 mm	Bore diameter bearing, upper tolerance
$d_{UT}$	-0,008 mm	Bore diameter bearing, lower tolerance
$D_{OT}$	0 mm	Outside diameter, upper tolerance
$D_{UT}$	-0,009 mm	Outside diameter, lower tolerance
$B_{OT}$	0 mm	Width inner ring, upper tolerance
$B_{UT}$	-0,12 mm	Width inner ring, lower tolerance
$C_{OT}$	0 mm	Width outer ring, upper tolerance
$C_{UT}$	-0,24 mm	Width outer ring, lower tolerance

### Mounting dimensions

$r_{1smin}$	0,3 mm	Edge Spacing
$r_{2smin}$	0,3 mm	Edge Spacing
$d_{amax}$	14,9 mm	Connection measure Inner ring
$D_{amin}$	17,5 mm	Housing Connection Diameter

### Temperature range

$T_{min}$	-50 °C	Operating temperature min.
$T_{max}$	200 °C	Operating temperature max.