12.10.2021, 15:22:50 (GMT+08:00) SCHAEFFLER



### FAG


# **UCFC213**


# Flanged housing unit

Schaeffler ID: 0822519750000

Flanged housing unit UCFC

## Technical information





#### **Dimensions**

А	36 mm	Height housing
A <sub>1</sub>	15 mm	Thickness of flange
A <sub>2</sub>	16 mm	Distance raceway
В	5,1 mm	Width
Q	M6	Connection thread lubrication
	5,47 kg	Weight

#### **Main Dimensions & Performance Data**

d	65 mm	Bore diameter
Н	205 mm	Height flange
U	55,7 mm	Total height unit
C <sub>r</sub>	61.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	40.000 N	Basic static load rating, radial
C ur	2.090 N	Fatigue load limit, radial

### **Mounting dimensions**

J 170 mm Distance fixing bore	
J 170 mm Pitch circle diameter (holes)	
N 19 mm Fixing bore	
N <sub>1</sub> Distance fixing bore	
T <sub>1</sub> 14 mm Height spigot	
Z 145 mm Diameter spigot	
h8 Diameter spigot clearance	
n 4 Number of screwing holes	

### **Additional information**

1	Number of housings
FC213	Housing
UC213	Bearing designation

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product. For further information you can use the contact form on our website.