Regulation EC No 1907/2006 Art.31

Productname: SP 350 **Creationdate:** 29.06.17 Version: 1.0

Ref.Nr.: BDS002168_3_20170629 (EN) **Replaces:**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SP 350

Bulk

1.2. Relevant identified uses of the substance or mixture and uses advised against

Anti Corrosion Products

1.3. Details of the supplier of the safety data sheet

CRC Industries Europe byba Touwslagerstraat 1 9240 Zele Belgium

Tel.: +32(0)52/45.60.11 Fax.: +32(0)52/45.00.34 E-mail: hse@crcind.com

Subsidiaries		Tel	Fax
CRC Industries Finland Oy	Laurinkatu 57 A 23 B, 08100 Lohja	+358/(19)32.921	
CRC Industries France	6, avenue du marais, C.S. 90028, 95102 Argenteuil Cedex	01.34.11.20.00	01.34.11.09.96
CRC Industries Deutschland GmbH	Südring 9, D-76473 Iffezheim	(07229) 303 0	(07229)30 32 66
CRC INDUSTRIES IBERIA S.L.U.	GREMIO DEL CUERO-PARC.96, POLIGONO INDUSTR. DE HONTORIA, 40195 SEGOVIA	0034/921.427.546	0034/921.436.270
CRC Industries Sweden	Laxfiskevägen 16, 433 38 Partille	0046/31 706 84 80	0046/31 27 39 91

1.4. Emergency telephone number

CRC Industries Europe, Belgium: Tel.: +32(0)52/45.60.11 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical: Flammable liquid, category 3

Flammable liquid and vapour.

Classification is based on test data.

Health: Not classified



Regulation EC No 1907/2006 Art.31

Productname: SP 350 Creationdate: 29.06.17 Version: 1.0

Ref.Nr.: BDS002168 3 20170629 (EN) Replaces:

Classification based on calculation method. **Environment:** Not classified Classification based on calculation method.

Other hazards: Repeated exposure may cause skin dryness or cracking.

Other hazards: Not classified

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictogram(s):

Signal word:

Hazard statement(s): H226: Flammable liquid and vapour. Precautionary statement(s): P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P403/235 : Store in a well-ventilated place. Keep cool.

P501-2: Dispose of contents/container to an authorised waste collection point.

Supplemental Hazard

Repeated exposure may cause skin dryness or cracking. information:

2.3. Other hazards

No information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	01-2119456620- 43	-	(926- 141-6)	25- 50	Asp. Tox. 1	H304	B,Q
mineral oil (IP 346 DMSO extract < 3%)	-	-	-	10- 25	-	-	В
Distillates (petroleum), hydrotreated light; Kerosine - unspecified	01-2119456620- 43	64742- 47-8	265- 149-8	5-10	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1	H226,H336,H304	В,Р
sulfonic acids,petroleum,sodium salts	01-2119527859- 22	68608- 26-4	271- 781-5	1-5	Skin Irrit. 2, Eye Irrit. 2	H315,H319	

Explanation notes

B: substance with national established workplace exposure limit

P: not classified as carcinogen, less than 0.1% w/w benzene (Einecs-nr. 200-753-7)

Q: The CAS-no is only an indicative identifier to be used outside the EU for global inventory entries.



Regulation EC No 1907/2006 Art.31

SP 350 Productname: Creationdate: 29.06.17 Version: 1.0

Ref.Nr.: BDS002168 3 20170629 (EN) Replaces:

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

If substance has got into eyes, immediately wash out with plenty of water for Contact with eyes:

several minutes

Seek medical attention if irritation persists

Contact with skin: Wash with water and soap.

Seek medical attention if irritation persists

Inhalation: Fresh air, keep warm and at rest.

Seek medical attention if ill effects occur

Ingestion: Give plenty of water to drink

Seek medical advice

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: Excessive inhalation of solvent vapours may give rise to nausea, headaches

and dizziness

Ingestion: Symptoms: sore throat, abdominal pain, nausea, vomiting

Mildly irritating to skin Skin contact:

Symptoms: redness and pain

Mildly irritating to eyes Eye contact:

Symptoms: redness and pain

4.3. Indication of any immediate medical attention and special treatment needed

General Advice: If you feel unwell, seek medical advice (show the label where possible

If symptoms persist always call a doctor

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

May form explosive vapour/air mixtures Forms hazardous decomposition products CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes



Regulation EC No 1907/2006 Art.31

Productname: SP 350

Ref.Nr.: BDS002168_3_20170629 (EN)

Creationdate : Replaces:

29.06.17 Version : 1.0

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources

Ensure adequate ventilation

Wear suitable protective clothing including eye/face protection.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Equipment should be earthed

Use explosion-proof electrical/ventilating/lighting/.../equipment.

Use only non-sparking tools.

Do not breathe aerosols or vapours.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Wash thoroughly after use

Wear protective gloves/protective clothing/eye protection/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed, in a cool, well ventilated place.

Keep out of reach of children.

7.3. Specific end use(s)

Anti Corrosion Products

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



Regulation EC No 1907/2006 Art.31

Productname: SP 350

Ref.Nr.: BDS002168_3_20170629 (EN)

Creationdate : Replaces:

29.06.17 Version : 1.0

Exposure limits:

No information available

8.2. Exposure controls

Control procedures :	Ensure adequate ventilation			
	Keep away from heat and sources of ignition			
	Take precautionary measures against static discharges			
Personal protection :	Take precautions to avoid contact with skin and eyes when handling the product.			
	It is good practice to wear gloves and to provide adequate ventilation whenever using the product.			
	In all cases handle and use the product in accordance with good industrial hygiene practices.			
inhalation :	In case of insufficient ventilation, wear suitable respiratory equipment.			
recommended respiratory protection:	Air purifying respirator equiped with organic gas/vapor cartridge (type A)			
hands and skin :	If handled correctly skin exposure will be accidental. In such case the use of disposable gloves should be sufficient provided they are changed immediately after a splash or spill may occur. If intentional contact is expected reusable gloves should be used with a breakthrough time greater than the total duration of the product use.			
Recommended gloves:	Nitrile			
eyes:	Wear safety eyewear according to EN 166.			

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Apperance : physical state : Viscous liquid. colour : Off-white.

odour: Characteristic odor.
pH: Not applicable.
Boiling point/range: Not available.
Flash point: 57 °C (Closed Cup)
Evaporation rate: Not available.
Explosion limits: upper limit: Not available.
lower limit: Not available.

Vapour pressure :Not available.Relative density :0.86-0.87 g/cm3 (@ 20°C).

Solubility in water : Emulsifies with water

Auto-ignition : $> 200 \, ^{\circ}\text{C}$

Viscosity: 90 mPa.s (@ 20°C).

9.2. Other information

VOC = volatile organic compounds 432 g/l



Regulation EC No 1907/2006 Art.31

Productname: SP 350

BDS002168_3_20170629 (EN)

Creationdate : Replaces:

29.06.17 Version : 1.0

SECTION 10: Stability and reactivity

10.1. Reactivity

Ref.Nr.:

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

acute toxicity:	based on available data the classification criteria are not met
skin corrosion/irritation:	based on available data the classification criteria are not met
serious eye damage/irritation:	based on available data the classification criteria are not met
respiratory or skin sensitisation:	based on available data the classification criteria are not met
germ cell mutagenicity:	based on available data the classification criteria are not met
carcinogenicity:	based on available data the classification criteria are not met
toxicity for reproduction:	based on available data the classification criteria are not met
STOT-single exposure:	based on available data the classification criteria are not met
STOT repeated exposure:	based on available data the classification criteria are not met
aspiration hazard:	based on available data the classification criteria are not met

Information on likely routes of exposure:

Inhalation :	Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Skin contact :	Prolonged skin contact will result in defatting of the skin, leading to irritation,
	and in some cases, dermatitis



Regulation EC No 1907/2006 Art.31

SP 350 Productname: **Creationdate:** 29.06.17 Version: 1.0

BDS002168_3_20170629 (EN) Ref.Nr.: Replaces:

Eye contact: May cause irritation.

Toxicological data:

Hazardous ingredient	CAS-nr.	method	
Distillates (petroleum), hydrotreated light; Kerosine - unspecified	64742-47-8	LD50 oral rat	> 2000 mg/kg
		LD50 derm.rabit	> 2000 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	-	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	>5000 mg/kg
		LD50 derm.rabit	> 5000 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Not classified

Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	-	IC50 algae	1000 mg/l
		LC50 fish	1000 mg/l
		EC50 daphnia	1000 mg/l

12.2. Persistence and degradability

No experimental data available

12.3. Bioaccumulative potential

No experimental data available

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

No experimental data available

SECTION 13: Disposal considerations



Ref.Nr.:

Regulation EC No 1907/2006 Art.31

Productname: SP 350

BDS002168_3_20170629 (EN)

Creationdate:

29.06.17 Version: 1.0

Replaces:

13.1. Waste treatment methods

Product: This material and its container must be disposed of in a safe way.

Do not discharge into drains or the environment, dispose to an authorised

waste collection point.

National regulations: Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number: 1268

14.2. UN proper shipping name

PETROLEUM PRODUCTS, N.O.S. (solvent naphtha) Proper shipping name:

14.3. Transport hazard class(es)

Class: 3 F1 ADR/RID - Classification code:

14.4. Packing group

Ш Packing group:

14.5. Environmental hazards

ADR/RID - Environmentally No hazardous: IMDG - Marine pollutant: No IATA/ICAO - Environmentally No hazardous:

14.6. Special precautions for user

ADR/RID - Tunnelcode: (D/E) F-E, S-E IMDG - Ems: IATA/ICAO - PAX: 355 IATA/ICAO - CAO 366

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



Regulation EC No 1907/2006 Art.31

Productname: SP 350 Creationdate: 29.06.17 Version: 1.0

Ref.Nr.: BDS002168_3_20170629 (EN) **Replaces:**

The Safety Data Sheet is compiled according to the current European requirements.

Regulation (EC) No 1907/2006 (REACH) Regulation (EC) No 1272/2008 (CLP)

European data	
Storage Class:	Storage Class 3: Flammable liquids
Storage Class:	Storage Class 3: Flammable liquids
Storage Class:	Storage Class 3: Flammable liquids
Storage Class:	Storage Class 3: Flammable liquids

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation hazard statements: -:-

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

acronyms and synonyms: TWA = time weight average

STEL = short time exposure limit VOC = volatile organic compounds PBT = persistant bioaccumulative toxic vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks,no part of these documents may be reproduced by any process without written permission from CRC.

