

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer		: Astraprom d.o.o.			
Product line		: W22		Product code : 12867461	
Frame	: 90L	Cooling method	: IC411 - TEFC		
Insulation class	: F	Mounting	: B3T		
Duty cycle	: S1	Rotation ¹	: Both (CW and CCW)		
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line		
Altitude	: 1000 m.a.s.l.	Approx. weight ²	: 23.3 kg		
Protection degree	: IP55	Moment of inertia (J)	: 0.0066 kgm ²		
Design	: N				
Output [kW]	1.5	1.5	1.5	1.5	1.5
Poles	4	4	4	4	4
Frequency [Hz]	50	50	50	50	60
Rated voltage [V]	220/380	230/400	240/415	460	
Rated current [A]	5.84/3.38	5.81/3.34	5.79/3.35	2.94	
L. R. Amperes [A]	40.3/23.3	43.0/24.7	45.8/26.5	25.0	
LRC [A]	6.9	7.4	7.9	8.5	
No load current [A]	3.28/1.90	3.83/2.20	4.15/2.40	2.00	
Rated speed [RPM]	1445	1450	1455	1755	
Slip [%]	3.67	3.33	3.00	2.50	
Rated torque [kgfm]	1.01	1.01	1.00	0.832	
Locked rotor torque [%]	260	290	310	340	
Breakdown torque [%]	300	320	350	409	
Service factor	1.00	1.00	1.00	1.00	
Temperature rise	80 K	80 K	80 K	80 K	
Locked rotor time	21s (cold) 12s (hot)	19s (cold) 11s (hot)	18s (cold) 10s (hot)	19s (cold) 11s (hot)	
Noise level ²	49.0 dB(A)	49.0 dB(A)	49.0 dB(A)	51.0 dB(A)	
Efficiency (%)	25%				
	50%	84.0	82.0	81.0	82.5
	75%	85.3	84.0	84.0	85.5
	100%	85.3	85.3	85.3	86.5
Power Factor	25%				
	50%	0.59	0.55	0.50	0.53
	75%	0.72	0.68	0.63	0.65
	100%	0.79	0.76	0.73	0.74
Losses at normative operating points (speed;torque), in percentage of rated output power					
Losses (%)	P1 (0,9;1,0)	16.9	16.9	16.9	15.3
	P2 (0,5;1,0)	15.5	15.5	15.5	14.1
	P3 (0,25;1,0)	15.1	15.1	15.1	13.7
	P4 (0,9;0,5)	8.6	8.6	8.6	7.8
	P5 (0,5;0,5)	6.6	6.6	6.6	5.9
	P6 (0,5;0,25)	4.9	4.9	4.9	4.4
	P7 (0,25;0,25)	3.7	3.7	3.7	3.4
Bearing type	: Drive end 6205 ZZ	Non drive end 6204 ZZ	Foundation loads		
Sealing	: V'Ring	V'Ring	Max. traction	: 85 kgf	
Lubrication interval	: -	-	Max. compression	: 109 kgf	
Lubricant amount	: -	-			
Lubricant type	: Mobil Polyrex EM				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	20/02/2023			1 / 19	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Notes

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	20/02/2023		2 / 19	

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer : Astraprom d.o.o.

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by				Page 3 / 19
Checked by				
Date	20/02/2023			
				Revision

TORQUE AND CURRENT VS SPEED CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22

Product code : 12867461



Performance : 220/380 V 50 Hz 4P

Rated current	: 5.84/3.38 A	Moment of inertia (J)	: 0.0066 kgm ²
LRC	: 6.9	Duty cycle	: S1
Rated torque	: 1.01 kgfm	Insulation class	: F
Locked rotor torque	: 260 %	Service factor	: 1.00
Breakdown torque	: 300 %	Temperature rise	: 80 K
Rated speed	: 1445 rpm	Design	: N

Locked rotor time : 21s (cold) 12s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 4 / 19	Revision
Checked by				
Date	20/02/2023			

TORQUE AND CURRENT VS SPEED CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22

Product code : 12867461



Performance : 230/400 V 50 Hz 4P

Rated current	: 5.81/3.34 A	Moment of inertia (J)	: 0.0066 kgm ²
LRC	: 7.4	Duty cycle	: S1
Rated torque	: 1.01 kgfm	Insulation class	: F
Locked rotor torque	: 290 %	Service factor	: 1.00
Breakdown torque	: 320 %	Temperature rise	: 80 K
Rated speed	: 1450 rpm	Design	: N

Locked rotor time : 19s (cold) 11s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 5 / 19	Revision
Checked by				
Date	20/02/2023			

TORQUE AND CURRENT VS SPEED CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22

Product code : 12867461



Performance : 240/415 V 50 Hz 4P

Rated current	: 5.79/3.35 A	Moment of inertia (J)	: 0.0066 kgm ²
LRC	: 7.9	Duty cycle	: S1
Rated torque	: 1.00 kgfm	Insulation class	: F
Locked rotor torque	: 310 %	Service factor	: 1.00
Breakdown torque	: 350 %	Temperature rise	: 80 K
Rated speed	: 1455 rpm	Design	: N

Locked rotor time : 18s (cold) 10s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		6 / 19		
Date	20/02/2023			

TORQUE AND CURRENT VS SPEED CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22

Product code : 12867461



Performance : 460 V 60 Hz 4P

Rated current	: 2.94 A	Moment of inertia (J)	: 0.0066 kgm ²
LRC	: 8.5	Duty cycle	: S1
Rated torque	: 0.832 kgfm	Insulation class	: F
Locked rotor torque	: 340 %	Service factor	: 1.00
Breakdown torque	: 409 %	Temperature rise	: 80 K
Rated speed	: 1755 rpm	Design	: N

Locked rotor time : 19s (cold) 11s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		7 / 19		
Date	20/02/2023			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22

Product code : 12867461



Performance : 220/380 V 50 Hz 4P

Rated current : 5.84/3.38 A
 LRC : 6.9
 Rated torque : 1.01 kgfm
 Locked rotor torque : 260 %
 Breakdown torque : 300 %
 Rated speed : 1445 rpm

Moment of inertia (J) : 0.0066 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 8 / 19	Revision
Checked by				
Date	20/02/2023			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22

Product code : 12867461



Performance : 230/400 V 50 Hz 4P

Rated current : 5.81/3.34 A
 LRC : 7.4
 Rated torque : 1.01 kgfm
 Locked rotor torque : 290 %
 Breakdown torque : 320 %
 Rated speed : 1450 rpm

Moment of inertia (J) : 0.0066 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22

Product code : 12867461



Performance : 240/415 V 50 Hz 4P

Rated current : 5.79/3.35 A
 LRC : 7.9
 Rated torque : 1.00 kgfm
 Locked rotor torque : 310 %
 Breakdown torque : 350 %
 Rated speed : 1455 rpm

Moment of inertia (J) : 0.0066 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				
			10 / 19	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22

Product code : 12867461



Performance : 460 V 60 Hz 4P

Rated current : 2.94 A
 LRC : 8.5
 Rated torque : 0.832 kgfm
 Locked rotor torque : 340 %
 Breakdown torque : 409 %
 Rated speed : 1755 rpm

Moment of inertia (J) : 0.0066 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		11 / 19		
Date		20/02/2023		

THERMAL LIMIT CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22

Product code : 12867461



Performance : 220/380 V 50 Hz 4P

Rated current : 5.84/3.38 A
 LRC : 6.9
 Rated torque : 1.01 kgfm
 Locked rotor torque : 260 %
 Breakdown torque : 300 %
 Rated speed : 1445 rpm

Moment of inertia (J) : 0.0066 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		12 / 19		
Date		20/02/2023		

THERMAL LIMIT CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22

Product code : 12867461



Performance : 230/400 V 50 Hz 4P

Rated current : 5.81/3.34 A
 LRC : 7.4
 Rated torque : 1.01 kgfm
 Locked rotor torque : 290 %
 Breakdown torque : 320 %
 Rated speed : 1450 rpm

Moment of inertia (J) : 0.0066 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date				
		Page	Revision	
		13 / 19		

THERMAL LIMIT CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22

Product code : 12867461



Performance : 240/415 V 50 Hz 4P

Rated current : 5.79/3.35 A
 LRC : 7.9
 Rated torque : 1.00 kgfm
 Locked rotor torque : 310 %
 Breakdown torque : 350 %
 Rated speed : 1455 rpm

Moment of inertia (J) : 0.0066 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		14 / 19		
Date		20/02/2023		

THERMAL LIMIT CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22

Product code : 12867461



Performance : 460 V 60 Hz 4P

Rated current : 2.94 A
 LRC : 8.5
 Rated torque : 0.832 kgfm
 Locked rotor torque : 340 %
 Breakdown torque : 409 %
 Rated speed : 1755 rpm

Moment of inertia (J) : 0.0066 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date				
		Page	Revision	
		15 / 19		

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22

Product code : 12867461



Performance : 220/380 V 50 Hz 4P

Rated current : 5.84/3.38 A
 LRC : 6.9
 Rated torque : 1.01 kgfm
 Locked rotor torque : 260 %
 Breakdown torque : 300 %
 Rated speed : 1445 rpm

Moment of inertia (J) : 0.0066 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 16 / 19	Revision
Checked by				
Date	20/02/2023			

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22

Product code : 12867461



Performance : 230/400 V 50 Hz 4P

Rated current : 5.81/3.34 A
 LRC : 7.4
 Rated torque : 1.01 kgfm
 Locked rotor torque : 290 %
 Breakdown torque : 320 %
 Rated speed : 1450 rpm

Moment of inertia (J) : 0.0066 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 17 / 19	Revision
Checked by				
Date	20/02/2023			

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22

Product code : 12867461



Performance : 240/415 V 50 Hz 4P

Rated current : 5.79/3.35 A
 LRC : 7.9
 Rated torque : 1.00 kgfm
 Locked rotor torque : 310 %
 Breakdown torque : 350 %
 Rated speed : 1455 rpm

Moment of inertia (J) : 0.0066 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 18 / 19	Revision
Checked by				
Date	20/02/2023			

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22

Product code : 12867461



Performance : 460 V 60 Hz 4P

Rated current : 2.94 A
 LRC : 8.5
 Rated torque : 0.832 kgfm
 Locked rotor torque : 340 %
 Breakdown torque : 409 %
 Rated speed : 1755 rpm

Moment of inertia (J) : 0.0066 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				