



FAG

## NUP217-E-XL-TVP2


Cylindrical roller bearing

Schaeffler ID:  
0167408580000

Cylindrical roller bearing NUP.-E-XL-TVP2, with cage, single row, locating bearing, 2 ribs on outer ring, 1 rib on inner ring, rib washer internal, type NUP

X-life

## Technical information



## Main Dimensions &amp; Performance Data

d	85 mm	Bore diameter
D	150 mm	Outside diameter
B	28 mm	Width
$C_r$	194.000 N	Basic dynamic load rating, radial
$C_{0r}$	194.000 N	Basic static load rating, radial
$C_{ur}$	34.000 N	Fatigue load limit, radial
$n_G$	6.400 1/min	Limiting speed
$n_{gr}$	4.000 1/min	Reference speed
	2,068 kg	Weight

## Mounting dimensions

$d_1$	107,5 mm	Maximum rib diameter inner ring
$D_{1\min}$	131,5 mm	Minimum rib diameter outer ring
$d_{a\min}$	96 mm	Minimum diameter shaft shoulder
$d_{c\min}$	110 mm	Minimum shaft shoulder
$D_{a\max}$	139 mm	Maximum diameter of housing shoulder
$r_{a\max}$	2 mm	Maximum recess radius

## Dimensions

$r_{\min}$	2 mm	Minimum chamfer dimension
$r_{1\min}$	2 mm	Minimum chamfer dimension
E	136,5 mm	Raceway diameter outer ring
F	100,5 mm	Raceway diameter inner ring
$B_3$	4,5 mm	Width of loose rib

## Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

