

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer		: Astraprom d.o.o.			
Product line		: Multimounting IE3 Three-Phase		Product code : 15448742	
Frame	: S132S	Cooling method	: IC411 - TEFC		
Insulation class	: F	Mounting	: B5T		
Duty cycle	: S1	Rotation <sup>1</sup>	: Both (CW and CCW)		
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line		
Altitude	: 1000 m.a.s.l.	Approx. weight <sup>3</sup>	: 62.3 kg		
Protection degree	: IP55	Moment of inertia (J)	: 0.0528 kgm <sup>2</sup>		
Design	: N				
Output [kW]	5.5	5.5	5.5	5.5	5.5
Poles	4	4	4	4	4
Frequency [Hz]	50	50	50	50	60
Rated voltage [V]	220/380	230/400	240/415	460	
Rated current [A]	18.5/10.7	18.1/10.4	17.8/10.3	9.07	
L. R. Amperes [A]	157/90.9	154/88.4	151/87.6	80.7	
LRC [A]	8.5	8.5	8.5	8.9	
No load current [A]	7.60/4.40	8.17/4.70	8.82/5.10	4.43	
Rated speed [RPM]	1460	1465	1470	1765	
Slip [%]	2.67	2.33	2.00	1.94	
Rated torque [kgfm]	3.67	3.66	3.64	3.04	
Locked rotor torque [%]	210	240	260	260	
Breakdown torque [%]	300	340	370	430	
Service factor	1.00	1.00	1.00	1.25	
Temperature rise	80 K	80 K	80 K	80 K	
Locked rotor time	27s (cold) 15s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)	32s (cold) 18s (hot)	
Noise level <sup>2</sup>	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	58.0 dB(A)	
Efficiency (%)	25%				
	50%	89.0	89.0	89.0	88.5
	75%	89.5	89.5	89.5	91.0
	100%	89.6	89.6	89.6	91.7
Power Factor	25%				
	50%	0.71	0.67	0.64	0.65
	75%	0.82	0.79	0.76	0.77
	100%	0.87	0.85	0.83	0.83
Losses at normative operating points (speed;torque), in percentage of rated output power					
Losses (%)	P1 (0,9;1,0)	10.5	10.0	9.9	8.9
	P2 (0,5;1,0)	9.2	8.8	8.7	7.8
	P3 (0,25;1,0)	8.8	8.4	8.3	7.4
	P4 (0,9;0,5)	4.9	4.7	4.7	4.2
	P5 (0,5;0,5)	3.5	3.4	3.3	3.0
	P6 (0,5;0,25)	2.3	2.2	2.2	1.9
	P7 (0,25;0,25)	1.6	1.6	1.6	1.4
Bearing type	: Drive end 6308 ZZ	Non drive end 6207 ZZ	Foundation loads		
Sealing	: Oil Seal	Oil Seal	Max. traction	: 210 kgf	
Lubrication interval	: -	-	Max. compression	: 272 kgf	
Lubricant amount	: -	-			
Lubricant type	: Mobil Polyrex EM				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	17/10/2024			1 / 19	

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Notes

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	17/10/2024		2 / 19	

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer : Astraprom d.o.o.

### Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by				Page 3 / 19
Checked by				
Date	17/10/2024			
			Revision	


# TORQUE AND CURRENT VS SPEED CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase Product code : 15448742



Performance : 220/380 V 50 Hz 4P

Rated current	: 18.5/10.7 A	Moment of inertia (J)	: 0.0528 kgm <sup>2</sup>
LRC	: 8.5	Duty cycle	: S1
Rated torque	: 3.67 kgfm	Insulation class	: F
Locked rotor torque	: 210 %	Service factor	: 1.00
Breakdown torque	: 300 %	Temperature rise	: 80 K
Rated speed	: 1460 rpm	Design	: N

Locked rotor time : 27s (cold) 15s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 4 / 19	Revision
Checked by				
Date	17/10/2024			


# TORQUE AND CURRENT VS SPEED CURVE



## Three Phase Induction Motor - Squirrel Cage

Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase Product code : 15448742



Performance : 230/400 V 50 Hz 4P

Rated current	: 18.1/10.4 A	Moment of inertia (J)	: 0.0528 kgm <sup>2</sup>
LRC	: 8.5	Duty cycle	: S1
Rated torque	: 3.66 kgfm	Insulation class	: F
Locked rotor torque	: 240 %	Service factor	: 1.00
Breakdown torque	: 340 %	Temperature rise	: 80 K
Rated speed	: 1465 rpm	Design	: N

Locked rotor time : 27s (cold) 15s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 5 / 19	Revision
Checked by				
Date	17/10/2024			


# TORQUE AND CURRENT VS SPEED CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase Product code : 15448742



Performance : 240/415 V 50 Hz 4P

Rated current	: 17.8/10.3 A	Moment of inertia (J)	: 0.0528 kgm <sup>2</sup>
LRC	: 8.5	Duty cycle	: S1
Rated torque	: 3.64 kgfm	Insulation class	: F
Locked rotor torque	: 260 %	Service factor	: 1.00
Breakdown torque	: 370 %	Temperature rise	: 80 K
Rated speed	: 1470 rpm	Design	: N

Locked rotor time : 27s (cold) 15s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 6 / 19	Revision
Checked by				
Date	17/10/2024			


# TORQUE AND CURRENT VS SPEED CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase Product code : 15448742



Performance : 460 V 60 Hz 4P

Rated current	: 9.07 A	Moment of inertia (J)	: 0.0528 kgm <sup>2</sup>
LRC	: 8.9	Duty cycle	: S1
Rated torque	: 3.04 kgfm	Insulation class	: F
Locked rotor torque	: 260 %	Service factor	: 1.25
Breakdown torque	: 430 %	Temperature rise	: 80 K
Rated speed	: 1765 rpm	Design	: N

Locked rotor time : 32s (cold) 18s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 7 / 19	Revision
Checked by				
Date	17/10/2024			


# LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase Product code : 15448742



Performance : 220/380 V 50 Hz 4P

Rated current	: 18.5/10.7 A	Moment of inertia (J)	: 0.0528 kgm <sup>2</sup>
LRC	: 8.5	Duty cycle	: S1
Rated torque	: 3.67 kgfm	Insulation class	: F
Locked rotor torque	: 210 %	Service factor	: 1.00
Breakdown torque	: 300 %	Temperature rise	: 80 K
Rated speed	: 1460 rpm	Design	: N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by			8 / 19	
Date	17/10/2024			


# LOAD PERFORMANCE CURVE

## Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase Product code : 15448742



Performance : 230/400 V 50 Hz 4P

Rated current : 18.1/10.4 A  
 LRC : 8.5  
 Rated torque : 3.66 kgfm  
 Locked rotor torque : 240 %  
 Breakdown torque : 340 %  
 Rated speed : 1465 rpm

Moment of inertia (J) : 0.0528 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				


# LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase Product code : 15448742



Performance : 240/415 V 50 Hz 4P

Rated current : 17.8/10.3 A  
 LRC : 8.5  
 Rated torque : 3.64 kgfm  
 Locked rotor torque : 260 %  
 Breakdown torque : 370 %  
 Rated speed : 1470 rpm

Moment of inertia (J) : 0.0528 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 10 / 19	Revision
Checked by				
Date	17/10/2024			


# LOAD PERFORMANCE CURVE

## Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase Product code : 15448742



Performance : 460 V 60 Hz 4P

Rated current : 9.07 A  
 LRC : 8.9  
 Rated torque : 3.04 kgfm  
 Locked rotor torque : 260 %  
 Breakdown torque : 430 %  
 Rated speed : 1765 rpm

Moment of inertia (J) : 0.0528 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.25  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				
			11 / 19	


# THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase Product code : 15448742



Performance : 220/380 V 50 Hz 4P

Rated current : 18.5/10.7 A  
 LRC : 8.5  
 Rated torque : 3.67 kgfm  
 Locked rotor torque : 210 %  
 Breakdown torque : 300 %  
 Rated speed : 1460 rpm

Moment of inertia (J) : 0.0528 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 12 / 19	Revision
Checked by				
Date	17/10/2024			


# THERMAL LIMIT CURVE

## Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase Product code : 15448742



Performance : 230/400 V 50 Hz 4P

Rated current : 18.1/10.4 A  
 LRC : 8.5  
 Rated torque : 3.66 kgfm  
 Locked rotor torque : 240 %  
 Breakdown torque : 340 %  
 Rated speed : 1465 rpm

Moment of inertia (J) : 0.0528 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Heating constant  
 Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date				
		Page	Revision	
		13 / 19		


# THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase Product code : 15448742



Performance : 240/415 V 50 Hz 4P

Rated current : 17.8/10.3 A  
 LRC : 8.5  
 Rated torque : 3.64 kgfm  
 Locked rotor torque : 260 %  
 Breakdown torque : 370 %  
 Rated speed : 1470 rpm

Moment of inertia (J) : 0.0528 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Heating constant  
 Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by	17/10/2024	Page		Revision
Checked by		14 / 19		
Date				


# THERMAL LIMIT CURVE

## Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase Product code : 15448742



Performance : 460 V 60 Hz 4P

Rated current	: 9.07 A	Moment of inertia (J)	: 0.0528 kgm <sup>2</sup>
LRC	: 8.9	Duty cycle	: S1
Rated torque	: 3.04 kgfm	Insulation class	: F
Locked rotor torque	: 260 %	Service factor	: 1.25
Breakdown torque	: 430 %	Temperature rise	: 80 K
Rated speed	: 1765 rpm	Design	: N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 15 / 19	Revision
Checked by				
Date	17/10/2024			


# VFD OPERATION CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase Product code : 15448742



Performance : 220/380 V 50 Hz 4P


Rated current : 18.5/10.7 A  
 LRC : 8.5  
 Rated torque : 3.67 kgfm  
 Locked rotor torque : 210 %  
 Breakdown torque : 300 %  
 Rated speed : 1460 rpm

Moment of inertia (J) : 0.0528 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 16 / 19	Revision
Checked by				
Date	17/10/2024			


# VFD OPERATION CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase Product code : 15448742



Performance : 230/400 V 50 Hz 4P

Rated current : 18.1/10.4 A  
 LRC : 8.5  
 Rated torque : 3.66 kgfm  
 Locked rotor torque : 240 %  
 Breakdown torque : 340 %  
 Rated speed : 1465 rpm

Moment of inertia (J) : 0.0528 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				


# VFD OPERATION CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase Product code : 15448742



Performance : 240/415 V 50 Hz 4P

Rated current : 17.8/10.3 A  
 LRC : 8.5  
 Rated torque : 3.64 kgfm  
 Locked rotor torque : 260 %  
 Breakdown torque : 370 %  
 Rated speed : 1470 rpm

Moment of inertia (J) : 0.0528 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				


# VFD OPERATION CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase Product code : 15448742



Performance : 460 V 60 Hz 4P

Rated current	: 9.07 A	Moment of inertia (J)	: 0.0528 kgm <sup>2</sup>
LRC	: 8.9	Duty cycle	: S1
Rated torque	: 3.04 kgfm	Insulation class	: F
Locked rotor torque	: 260 %	Service factor	: 1.25
Breakdown torque	: 430 %	Temperature rise	: 80 K
Rated speed	: 1765 rpm	Design	: N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		19 / 19		
Date		17/10/2024		