



Technical information



23230-E1-XL-K-TVPB

Spherical roller bearing

Schaeffler ID:
0190361830000

Spherical roller bearings 232..-E1-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

Main Dimensions & Performance Data

d	150 mm	Bore diameter
D	270 mm	Outside diameter
B	96 mm	Width
C_r	1.280.000 N	Basic dynamic load rating, radial
C_{0r}	1.660.000 N	Basic static load rating, radial
C_{ur}	133.000 N	Fatigue load limit, radial
n_G	2.400 1/min	Limiting speed
n_{gr}	1.400 1/min	Reference speed
	21,842 kg	Weight

Mounting dimensions

$d_{a \min}$	164 mm	Minimum diameter shaft shoulder
$D_{a \max}$	256 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum recess radius
$B_{a \min}$	20 mm	Minimum cavity width of the sleeve
$d_{a \max}$	174 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	163 mm	Minimum cavity diameter of the sleeve

Dimensions

e	0,33	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
r_{\min}	3 mm	Minimum chamfer dimension
D_1	232,6 mm	Bore diameter outer ring
Y_1	2,02	Dynamic axial load factor
Y_2	3	Dynamic axial load factor
d_2	174 mm	Raceway diameter of the inner ring
Y_0	1,97	Static axial load factor
d_s	6,3 mm	Diameter lubrication hole
n_s	12,2 mm	Width of lubricating groove

Additional information

H2330	Adapter sleeve
AHX3230G	Withdrawal sleeve

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.