

FAG

★ 33020


Tapered roller bearing

Schaeffler ID:
0167134000000

★ Preferred product

Tapered roller bearings 330, main dimensions to DIN ISO 355 / DIN 720, separable, adjusted or in pairs

Technical information



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.
	2,411 kg	Weight

Main Dimensions & Performance Data

d	100 mm	Bore diameter
D	150 mm	Outside diameter
B	39 mm	Width, inner ring
C	32,5 mm	Width, outer ring
T	39 mm	Width, total
C _r	225.000 N	Basic dynamic load rating, radial
C _{0r}	395.000 N	Basic static load rating, radial
C _{ur}	48.500 N	Fatigue load limit, radial
n _G	4.450 1/min	Limiting speed
n _{gr}	2.900 1/min	Thermal speed rating

Dimensions

r _{1, 2 min}	2 mm	Minimum chamfer dimension of inner ring back face
r _{3, 4 min}	1,5 mm	Minimum chamfer dimension of outer ring back face
a	29 mm	Distance between the apexes of the pressure cones
d ₁	124,7 mm	Guidance rib diameter of inner ring

Mounting dimensions

d _{a max}	108 mm	Maximum diameter of shaft shoulder
d _{b min}	109 mm	Minimum diameter of shaft shoulder
D _{a min}	135 mm	Minimum diameter of housing shoulder
D _{a max}	141 mm	Maximum diameter of housing shoulder
D _{b min}	143 mm	Minimum diameter of housing shoulder
C _{a min}	7 mm	Minimum axial space
C _{b min}	6,5 mm	Minimum axial space
r _{a max}	2 mm	Maximum fillet radius of shaft
r _{b max}	1,5 mm	Maximum fillet radius of housing

Calculation factors

	T2CE100	Comparative designation to ISO 10317 and ISO 355
e	0,29	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	2,09	Dynamic axial load factor
Y ₀	1,15	Static axial load factor