

FAG


33207

Tapered roller bearing

Schaeffler ID:
0167139900000

Tapered roller bearings 332, main dimensions to DIN ISO 355 / DIN 720, separable, adjusted or in pairs

Technical information



Main Dimensions & Performance Data

d	35 mm	Bore diameter
D	72 mm	Outside diameter
B	28 mm	Width, inner ring
C	22 mm	Width, outer ring
T	28 mm	Width, total
C_r	86.000 N	Basic dynamic load rating, radial
C_{0r}	105.000 N	Basic static load rating, radial
C_{ur}	13.100 N	Fatigue load limit, radial
n_G	10.100 1/min	Limiting speed
n_{gr}	6.200 1/min	Thermal speed rating
	0,52 kg	Weight

Dimensions

$r_{1,2 \text{ min}}$	1,5 mm	Minimum chamfer dimension of inner ring back face
$r_{3,4 \text{ min}}$	1,5 mm	Minimum chamfer dimension of outer ring back face
a	18 mm	Distance between the apexes of the pressure cones
d_1	53 mm	Guidance rib diameter of inner ring

Mounting dimensions

$d_{a \text{ max}}$	42 mm	Maximum diameter of shaft shoulder
$d_{b \text{ min}}$	42 mm	Minimum diameter of shaft shoulder
$D_{a \text{ min}}$	61 mm	Minimum diameter of housing shoulder
$D_{a \text{ max}}$	65 mm	Maximum diameter of housing shoulder
$D_{b \text{ min}}$	68 mm	Minimum diameter of housing shoulder
$C_{a \text{ min}}$	5 mm	Minimum axial space
$C_{b \text{ min}}$	6 mm	Minimum axial space
$r_{a \text{ max}}$	1,5 mm	Maximum fillet radius of shaft
$r_{b \text{ max}}$	1,5 mm	Maximum fillet radius of housing

Temperature range

e	0,35	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
T _{min}	-30 °C	Operating temperature min.
Y	1,7	Dynamic axial load factor
T _{max}	120 °C	Operating temperature max.
Y ₀	0,93	Static axial load factor

Additional information

T2DE035	Comparative designation to ISO 10317 and ISO 355
---------	--