

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer		: Astraprom d.o.o.			
Product line		: W22 IE3 Three-Phase		Product code : 12862503	
Frame	: 280S/M	Cooling method	: IC411 - TEFC		
Insulation class	: F	Mounting	: B3T		
Duty cycle	: S1	Rotation ¹	: Both (CW and CCW)		
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line		
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 654 kg		
Protection degree	: IP55	Moment of inertia (J)	: 2.09 kgm ²		
Design	: N				
Output [kW]	75	75	75	75	
Poles	4	4	4	4	
Frequency [Hz]	50	50	50	60	
Rated voltage [V]	380/660	400/690	415	460	
Rated current [A]	141/81.2	135/78.3	134	119	
L. R. Amperes [A]	987/568	1013/587	1072	952	
LRC [A]	7.0	7.5	8.0	8.0	
No load current [A]	44.0/25.3	47.0/27.2	50.0	44.0	
Rated speed [RPM]	1485	1487	1488	1789	
Slip [%]					
Rated torque [kgfm]	49.2	49.1	49.1	40.8	
Locked rotor torque [%]	190	220	229	240	
Breakdown torque [%]	229	260	280	290	
Service factor	1.00	1.00	1.00	1.00	
Temperature rise	80 K	80 K	80 K	80 K	
Locked rotor time					
Noise level ²	69.0 dB(A)	69.0 dB(A)	69.0 dB(A)	73.0 dB(A)	
Efficiency (%)	25%				
	50%				
	75%				
	100%				
Power Factor	25%				
	50%				
	75%				
	100%				
Losses at normative operating points (speed;torque), in percentage of rated output power					
Losses (%)	P1 (0,9;1,0)	4.9	4.7	4.7	4.5
	P2 (0,5;1,0)	3.8	3.7	3.7	3.5
	P3 (0,25;1,0)	3.5	3.4	3.4	3.2
	P4 (0,9;0,5)	2.5	2.4	2.4	2.3
	P5 (0,5;0,5)	1.5	1.5	1.5	1.4
	P6 (0,5;0,25)	1.0	1.0	1.0	0.9
	P7 (0,25;0,25)	0.6	0.6	0.6	0.6
Bearing type	: Drive end : 6316 C3	Non drive end : 6316 C3	Foundation loads		
Sealing	: WSeal	WSeal	Max. traction : 709 kgf		
Lubrication interval	: 13000 h	13000 h	Max. compression : 1363 kgf		
Lubricant amount	: 34 g	34 g			
Lubricant type	: Mobil Polyrex EM				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	13/10/2023			1 / 19	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Notes

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	13/10/2023		2 / 19	

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer : Astraprom d.o.o.

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by				Page 3 / 19
Checked by				
Date	13/10/2023			
			Revision	

TORQUE AND CURRENT VS SPEED CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12862503



Performance : 380/660 V 50 Hz 4P

Rated current	: 141/81.2 A	Moment of inertia (J)	: 2.09 kgm ²
LRC	: 7.0	Duty cycle	: S1
Rated torque	: 49.2 kgfm	Insulation class	: F
Locked rotor torque	: 190 %	Service factor	: 1.00
Breakdown torque	: 229 %	Temperature rise	: 80 K
Rated speed	: 1485 rpm	Design	: N

Locked rotor time

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 4 / 19	Revision
Checked by				
Date	13/10/2023			

TORQUE AND CURRENT VS SPEED CURVE




Three Phase Induction Motor - Squirrel Cage

Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12862503



Performance : 400/690 V 50 Hz 4P

Rated current : 135/78.3 A
 LRC : 7.5
 Rated torque : 49.1 kgfm
 Locked rotor torque : 220 %
 Breakdown torque : 260 %
 Rated speed : 1487 rpm

Moment of inertia (J) : 2.09 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Locked rotor time

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date	13/10/2023			

TORQUE AND CURRENT VS SPEED CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12862503



Performance : 415 V 50 Hz 4P

Rated current	: 134 A	Moment of inertia (J)	: 2.09 kgm ²
LRC	: 8.0	Duty cycle	: S1
Rated torque	: 49.1 kgfm	Insulation class	: F
Locked rotor torque	: 229 %	Service factor	: 1.00
Breakdown torque	: 280 %	Temperature rise	: 80 K
Rated speed	: 1488 rpm	Design	: N

Locked rotor time

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 6 / 19	Revision
Checked by				
Date	13/10/2023			

TORQUE AND CURRENT VS SPEED CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12862503



Performance : 460 V 60 Hz 4P

Rated current	: 119 A	Moment of inertia (J)	: 2.09 kgm ²
LRC	: 8.0	Duty cycle	: S1
Rated torque	: 40.8 kgfm	Insulation class	: F
Locked rotor torque	: 240 %	Service factor	: 1.00
Breakdown torque	: 290 %	Temperature rise	: 80 K
Rated speed	: 1789 rpm	Design	: N

Locked rotor time

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date	13/10/2023			
			7 / 19	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12862503



Performance : 380/660 V 50 Hz 4P

Rated current : 141/81.2 A
 LRC : 7.0
 Rated torque : 49.2 kgfm
 Locked rotor torque : 190 %
 Breakdown torque : 229 %
 Rated speed : 1485 rpm

Moment of inertia (J) : 2.09 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 8 / 19	Revision
Checked by				
Date	13/10/2023			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12862503



Performance : 400/690 V 50 Hz 4P

Rated current : 135/78.3 A
 LRC : 7.5
 Rated torque : 49.1 kgfm
 Locked rotor torque : 220 %
 Breakdown torque : 260 %
 Rated speed : 1487 rpm

Moment of inertia (J) : 2.09 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12862503



Performance : 415 V 50 Hz 4P

Rated current	: 134 A	Moment of inertia (J)	: 2.09 kgm ²
LRC	: 8.0	Duty cycle	: S1
Rated torque	: 49.1 kgfm	Insulation class	: F
Locked rotor torque	: 229 %	Service factor	: 1.00
Breakdown torque	: 280 %	Temperature rise	: 80 K
Rated speed	: 1488 rpm	Design	: N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		10 / 19		
Date	13/10/2023			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12862503



Performance : 460 V 60 Hz 4P

Rated current : 119 A
 LRC : 8.0
 Rated torque : 40.8 kgfm
 Locked rotor torque : 240 %
 Breakdown torque : 290 %
 Rated speed : 1789 rpm

Moment of inertia (J) : 2.09 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		11 / 19		
Date		13/10/2023		

THERMAL LIMIT CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12862503



Performance : 380/660 V 50 Hz 4P

Rated current : 141/81.2 A
 LRC : 7.0
 Rated torque : 49.2 kgfm
 Locked rotor torque : 190 %
 Breakdown torque : 229 %
 Rated speed : 1485 rpm

Moment of inertia (J) : 2.09 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		12 / 19		
Date		13/10/2023		

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage




Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code :

12862503



Performance : 400/690 V 50 Hz 4P

Rated current : 135/78.3 A
 LRC : 7.5
 Rated torque : 49.1 kgfm
 Locked rotor torque : 220 %
 Breakdown torque : 260 %
 Rated speed : 1487 rpm

Moment of inertia (J) : 2.09 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date	13/10/2023			

THERMAL LIMIT CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12862503



Performance : 415 V 50 Hz 4P

Rated current	: 134 A	Moment of inertia (J)	: 2.09 kgm ²
LRC	: 8.0	Duty cycle	: S1
Rated torque	: 49.1 kgfm	Insulation class	: F
Locked rotor torque	: 229 %	Service factor	: 1.00
Breakdown torque	: 280 %	Temperature rise	: 80 K
Rated speed	: 1488 rpm	Design	: N

Heating constant
Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 14 / 19	Revision
Checked by				
Date	13/10/2023			

THERMAL LIMIT CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12862503



Performance : 460 V 60 Hz 4P

Rated current : 119 A
 LRC : 8.0
 Rated torque : 40.8 kgfm
 Locked rotor torque : 240 %
 Breakdown torque : 290 %
 Rated speed : 1789 rpm

Moment of inertia (J) : 2.09 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 15 / 19	Revision
Checked by				
Date	13/10/2023			

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12862503



Performance : 380/660 V 50 Hz 4P

Rated current : 141/81.2 A
 LRC : 7.0
 Rated torque : 49.2 kgfm
 Locked rotor torque : 190 %
 Breakdown torque : 229 %
 Rated speed : 1485 rpm

Moment of inertia (J) : 2.09 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12862503



Performance : 400/690 V 50 Hz 4P

Rated current : 135/78.3 A
 LRC : 7.5
 Rated torque : 49.1 kgfm
 Locked rotor torque : 220 %
 Breakdown torque : 260 %
 Rated speed : 1487 rpm

Moment of inertia (J) : 2.09 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 17 / 19	Revision
Checked by				
Date	13/10/2023			

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12862503



Performance : 415 V 50 Hz 4P

Rated current	: 134 A	Moment of inertia (J)	: 2.09 kgm ²
LRC	: 8.0	Duty cycle	: S1
Rated torque	: 49.1 kgfm	Insulation class	: F
Locked rotor torque	: 229 %	Service factor	: 1.00
Breakdown torque	: 280 %	Temperature rise	: 80 K
Rated speed	: 1488 rpm	Design	: N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		18 / 19		
Date	13/10/2023			

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12862503



Performance : 460 V 60 Hz 4P

Rated current : 119 A
 LRC : 8.0
 Rated torque : 40.8 kgfm
 Locked rotor torque : 240 %
 Breakdown torque : 290 %
 Rated speed : 1789 rpm

Moment of inertia (J) : 2.09 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		19 / 19		
Date		13/10/2023		