

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer		: Astraprom d.o.o.			
Product line		: IE3 Three-Phase		Product code : 12862750	
Frame	: 160L	Cooling method	: IC411 - TEFC		
Insulation class	: F	Mounting	: B3T		
Duty cycle	: S1	Rotation <sup>1</sup>	: Both (CW and CCW)		
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line		
Altitude	: 1000 m.a.s.l.	Approx. weight <sup>2</sup>	: 148 kg		
Protection degree	: IP55	Moment of inertia (J)	: 0.1931 kgm <sup>2</sup>		
Design	: N				
Output [kW]	11	11	11	11	
Poles	6	6	6	6	
Frequency [Hz]	50	50	50	60	
Rated voltage [V]	380/660	400/690	415	460	
Rated current [A]	23.1/13.3	22.8/13.2	22.9	20.1	
L. R. Amperes [A]	157/90.4	162/93.8	169	157	
LRC [A]	6.8	7.1	7.4	7.8	
No load current [A]	12.5/7.20	14.0/8.12	15.5	13.0	
Rated speed [RPM]	975	978	980	1182	
Slip [%]	2.50	2.20	2.00	1.50	
Rated torque [kgfm]	11.0	11.0	10.9	9.06	
Locked rotor torque [%]	250	280	310	350	
Breakdown torque [%]	270	300	330	370	
Service factor	1.00	1.00	1.00	1.00	
Temperature rise	80 K	80 K	80 K	80 K	
Locked rotor time	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	
Noise level <sup>2</sup>	57.0 dB(A)	57.0 dB(A)	57.0 dB(A)	59.0 dB(A)	
Efficiency (%)	25%				
	50%	89.7	89.0	88.3	88.6
	75%	90.3	90.1	89.8	90.4
	100%	90.3	90.5	90.5	91.7
Power Factor	25%				
	50%	0.60	0.56	0.53	0.54
	75%	0.73	0.70	0.67	0.67
	100%	0.80	0.77	0.74	0.75
Losses at normative operating points (speed;torque), in percentage of rated output power					
Losses (%)	P1 (0,9;1,0)	10.5	10.3	10.3	8.9
	P2 (0,5;1,0)	9.4	9.2	9.2	7.9
	P3 (0,25;1,0)	9.1	8.9	8.9	7.7
	P4 (0,9;0,5)	5.3	5.2	5.2	4.5
	P5 (0,5;0,5)	4.0	3.9	3.9	3.3
	P6 (0,5;0,25)	2.8	2.7	2.7	2.4
	P7 (0,25;0,25)	2.1	2.0	2.0	1.8
Bearing type	: Drive end 6309 ZZ C3 Non drive end 6209 ZZ C3	Foundation loads			
Sealing	: V'Ring V'Ring	Max. traction : 454 kgf			
Lubrication interval	: - -	Max. compression : 602 kgf			
Lubricant amount	: - -				
Lubricant type	: Mobil Polyrex EM				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	07/11/2022			1 / 19	

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Notes

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	07/11/2022		2 / 19	

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer : Astraprom d.o.o.

### Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by				Page 3 / 19
Checked by				
Date	07/11/2022			
			Revision	

# TORQUE AND CURRENT VS SPEED CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : IE3 Three-Phase

Product code : 12862750



Performance : 380/660 V 50 Hz 6P

Rated current	: 23.1/13.3 A	Moment of inertia (J)	: 0.1931 kgm <sup>2</sup>
LRC	: 6.8	Duty cycle	: S1
Rated torque	: 11.0 kgfm	Insulation class	: F
Locked rotor torque	: 250 %	Service factor	: 1.00
Breakdown torque	: 270 %	Temperature rise	: 80 K
Rated speed	: 975 rpm	Design	: N

Locked rotor time : 21s (cold) 12s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		4 / 19		
Date	07/11/2022			

# TORQUE AND CURRENT VS SPEED CURVE




## Three Phase Induction Motor - Squirrel Cage

Customer : Astraprom d.o.o.

Product line : IE3 Three-Phase

Product code : 12862750



Performance : 400/690 V 50 Hz 6P

Rated current	: 22.8/13.2 A	Moment of inertia (J)	: 0.1931 kgm <sup>2</sup>
LRC	: 7.1	Duty cycle	: S1
Rated torque	: 11.0 kgfm	Insulation class	: F
Locked rotor torque	: 280 %	Service factor	: 1.00
Breakdown torque	: 300 %	Temperature rise	: 80 K
Rated speed	: 978 rpm	Design	: N

Locked rotor time : 21s (cold) 12s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 5 / 19	Revision
Checked by				
Date	07/11/2022			

# TORQUE AND CURRENT VS SPEED CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : IE3 Three-Phase

Product code : 12862750



Performance : 415 V 50 Hz 6P

Rated current	: 22.9 A	Moment of inertia (J)	: 0.1931 kgm <sup>2</sup>
LRC	: 7.4	Duty cycle	: S1
Rated torque	: 10.9 kgfm	Insulation class	: F
Locked rotor torque	: 310 %	Service factor	: 1.00
Breakdown torque	: 330 %	Temperature rise	: 80 K
Rated speed	: 980 rpm	Design	: N

Locked rotor time : 21s (cold) 12s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		6 / 19		
Date	07/11/2022			

# TORQUE AND CURRENT VS SPEED CURVE




## Three Phase Induction Motor - Squirrel Cage

Customer : Astraprom d.o.o.

Product line : IE3 Three-Phase

Product code : 12862750



Performance : 460 V 60 Hz 6P

Rated current	: 20.1 A	Moment of inertia (J)	: 0.1931 kgm <sup>2</sup>
LRC	: 7.8	Duty cycle	: S1
Rated torque	: 9.06 kgfm	Insulation class	: F
Locked rotor torque	: 350 %	Service factor	: 1.00
Breakdown torque	: 370 %	Temperature rise	: 80 K
Rated speed	: 1182 rpm	Design	: N

Locked rotor time : 21s (cold) 12s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		7 / 19		
Date	07/11/2022			

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : IE3 Three-Phase

Product code : 12862750



Performance : 380/660 V 50 Hz 6P

Rated current : 23.1/13.3 A  
 LRC : 6.8  
 Rated torque : 11.0 kgfm  
 Locked rotor torque : 250 %  
 Breakdown torque : 270 %  
 Rated speed : 975 rpm

Moment of inertia (J) : 0.1931 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : IE3 Three-Phase

Product code : 12862750



Performance : 400/690 V 50 Hz 6P

Rated current : 22.8/13.2 A  
 LRC : 7.1  
 Rated torque : 11.0 kgfm  
 Locked rotor torque : 280 %  
 Breakdown torque : 300 %  
 Rated speed : 978 rpm

Moment of inertia (J) : 0.1931 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : IE3 Three-Phase

Product code : 12862750



Performance : 415 V 50 Hz 6P

Rated current : 22.9 A  
 LRC : 7.4  
 Rated torque : 10.9 kgfm  
 Locked rotor torque : 310 %  
 Breakdown torque : 330 %  
 Rated speed : 980 rpm

Moment of inertia (J) : 0.1931 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 10 / 19	Revision
Checked by				
Date	07/11/2022			

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : IE3 Three-Phase

Product code : 12862750



Performance : 460 V 60 Hz 6P

Rated current : 20.1 A  
 LRC : 7.8  
 Rated torque : 9.06 kgfm  
 Locked rotor torque : 350 %  
 Breakdown torque : 370 %  
 Rated speed : 1182 rpm

Moment of inertia (J) : 0.1931 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		11 / 19		
Date		07/11/2022		

# THERMAL LIMIT CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : IE3 Three-Phase

Product code : 12862750



Performance : 380/660 V 50 Hz 6P

Rated current : 23.1/13.3 A  
 LRC : 6.8  
 Rated torque : 11.0 kgfm  
 Locked rotor torque : 250 %  
 Breakdown torque : 270 %  
 Rated speed : 975 rpm

Moment of inertia (J) : 0.1931 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Heating constant  
 Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date				
		Page	Revision	
		12 / 19		

# THERMAL LIMIT CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : IE3 Three-Phase

Product code : 12862750



Performance : 400/690 V 50 Hz 6P

Rated current : 22.8/13.2 A  
 LRC : 7.1  
 Rated torque : 11.0 kgfm  
 Locked rotor torque : 280 %  
 Breakdown torque : 300 %  
 Rated speed : 978 rpm

Moment of inertia (J) : 0.1931 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Heating constant  
 Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date				
		Page	Revision	
		13 / 19		

# THERMAL LIMIT CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : IE3 Three-Phase

Product code : 12862750



Performance : 415 V 50 Hz 6P

Rated current	: 22.9 A	Moment of inertia (J)	: 0.1931 kgm <sup>2</sup>
LRC	: 7.4	Duty cycle	: S1
Rated torque	: 10.9 kgfm	Insulation class	: F
Locked rotor torque	: 310 %	Service factor	: 1.00
Breakdown torque	: 330 %	Temperature rise	: 80 K
Rated speed	: 980 rpm	Design	: N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		14 / 19		
Date	07/11/2022			

# THERMAL LIMIT CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : IE3 Three-Phase

Product code : 12862750



Performance : 460 V 60 Hz 6P

Rated current : 20.1 A  
 LRC : 7.8  
 Rated torque : 9.06 kgfm  
 Locked rotor torque : 350 %  
 Breakdown torque : 370 %  
 Rated speed : 1182 rpm

Moment of inertia (J) : 0.1931 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 15 / 19	Revision
Checked by				
Date	07/11/2022			

# VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : IE3 Three-Phase

Product code : 12862750



Performance : 380/660 V 50 Hz 6P

Rated current : 23.1/13.3 A  
 LRC : 6.8  
 Rated torque : 11.0 kgfm  
 Locked rotor torque : 250 %  
 Breakdown torque : 270 %  
 Rated speed : 975 rpm

Moment of inertia (J) : 0.1931 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 16 / 19	Revision
Checked by				
Date	07/11/2022			

# VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : IE3 Three-Phase

Product code : 12862750



Performance : 400/690 V 50 Hz 6P

Rated current : 22.8/13.2 A  
 LRC : 7.1  
 Rated torque : 11.0 kgfm  
 Locked rotor torque : 280 %  
 Breakdown torque : 300 %  
 Rated speed : 978 rpm

Moment of inertia (J) : 0.1931 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 17 / 19	Revision
Checked by				
Date	07/11/2022			

# VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : IE3 Three-Phase

Product code : 12862750



Performance : 415 V 50 Hz 6P

Rated current	: 22.9 A	Moment of inertia (J)	: 0.1931 kgm <sup>2</sup>
LRC	: 7.4	Duty cycle	: S1
Rated torque	: 10.9 kgfm	Insulation class	: F
Locked rotor torque	: 310 %	Service factor	: 1.00
Breakdown torque	: 330 %	Temperature rise	: 80 K
Rated speed	: 980 rpm	Design	: N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		18 / 19		
Date	07/11/2022			

# VFD OPERATION CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : IE3 Three-Phase

Product code : 12862750



Performance : 460 V 60 Hz 6P

Rated current : 20.1 A  
 LRC : 7.8  
 Rated torque : 9.06 kgfm  
 Locked rotor torque : 350 %  
 Breakdown torque : 370 %  
 Rated speed : 1182 rpm

Moment of inertia (J) : 0.1931 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		19 / 19		
Date		07/11/2022		