

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer		: Astraprom d.o.o.			
Product line		: W22 IE3 Three-Phase		Product code : 12867529	
Frame	: 132M	Cooling method	: IC411 - TEFC		
Insulation class	: F	Mounting	: B3T		
Duty cycle	: S1	Rotation <sup>1</sup>	: Both (CW and CCW)		
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line		
Altitude	: 1000 m.a.s.l.	Approx. weight <sup>2</sup>	: 75.7 kg		
Protection degree	: IP55	Moment of inertia (J)	: 0.0563 kgm <sup>2</sup>		
Design	: N				
Output [kW]	7.5	7.5	7.5	7.5	7.5
Poles	4	4	4	4	4
Frequency [Hz]	50	50	50	50	60
Rated voltage [V]	380/660	400/690	415	415	460
Rated current [A]	14.8/8.52	14.4/8.35	14.2	14.2	12.7
L. R. Amperes [A]	123/70.7	122/71.0	124	124	121
LRC [A]	8.3	8.5	8.7	8.7	9.5
No load current [A]	6.80/3.92	7.50/4.35	8.30	8.30	6.90
Rated speed [RPM]	1460	1465	1465	1465	1770
Slip [%]	2.67	2.33	2.33	2.33	1.67
Rated torque [kgfm]	5.00	4.99	4.99	4.99	4.13
Locked rotor torque [%]	220	240	260	260	280
Breakdown torque [%]	310	350	380	380	400
Service factor	1.00	1.00	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	80 K
Locked rotor time	19s (cold) 11s (hot)	18s (cold) 10s (hot)	16s (cold) 9s (hot)	16s (cold) 9s (hot)	21s (cold) 12s (hot)
Noise level <sup>2</sup>	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	58.0 dB(A)
Efficiency (%)	25%				
	50%	90.0	89.0	88.5	90.1
	75%	90.2	90.4	90.3	91.2
	100%	90.4	90.4	90.4	91.7
Power Factor	25%				
	50%	0.66	0.63	0.60	0.62
	75%	0.79	0.76	0.73	0.74
	100%	0.85	0.83	0.81	0.81
Losses at normative operating points (speed;torque), in percentage of rated output power					
Losses (%)	P1 (0,9;1,0)	10.5	10.5	10.5	9.0
	P2 (0,5;1,0)	9.5	9.5	9.5	8.1
	P3 (0,25;1,0)	9.2	9.2	9.2	7.9
	P4 (0,9;0,5)	5.0	5.0	5.0	4.2
	P5 (0,5;0,5)	3.7	3.7	3.7	3.2
	P6 (0,5;0,25)	2.5	2.5	2.5	2.1
	P7 (0,25;0,25)	1.9	1.9	1.9	1.6
Bearing type	: Drive end 6308 ZZ	Non drive end 6207 ZZ	Foundation loads		
Sealing	: V'Ring	V'Ring	Max. traction	: 267 kgf	
Lubrication interval	: -	-	Max. compression	: 343 kgf	
Lubricant amount	: -	-			
Lubricant type	: Mobil Polyrex EM				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	24/10/2023			1 / 19	

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Notes

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	24/10/2023		2 / 19	

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer : Astraprom d.o.o.

### Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by				Page 3 / 19
Checked by				
Date	24/10/2023			
				Revision

# TORQUE AND CURRENT VS SPEED CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12867529



Performance : 380/660 V 50 Hz 4P

Rated current	: 14.8/8.52 A	Moment of inertia (J)	: 0.0563 kgm <sup>2</sup>
LRC	: 8.3	Duty cycle	: S1
Rated torque	: 5.00 kgfm	Insulation class	: F
Locked rotor torque	: 220 %	Service factor	: 1.00
Breakdown torque	: 310 %	Temperature rise	: 80 K
Rated speed	: 1460 rpm	Design	: N

Locked rotor time : 19s (cold) 11s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 4 / 19	Revision
Checked by				
Date	24/10/2023			

# TORQUE AND CURRENT VS SPEED CURVE

Three Phase Induction Motor - Squirrel Cage




Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code :

12867529



Performance : 400/690 V 50 Hz 4P

Rated current : 14.4/8.35 A  
 LRC : 8.5  
 Rated torque : 4.99 kgfm  
 Locked rotor torque : 240 %  
 Breakdown torque : 350 %  
 Rated speed : 1465 rpm

Moment of inertia (J) : 0.0563 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Locked rotor time : 18s (cold) 10s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date	24/10/2023			

# TORQUE AND CURRENT VS SPEED CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12867529



Performance : 415 V 50 Hz 4P

Rated current	: 14.2 A	Moment of inertia (J)	: 0.0563 kgm <sup>2</sup>
LRC	: 8.7	Duty cycle	: S1
Rated torque	: 4.99 kgfm	Insulation class	: F
Locked rotor torque	: 260 %	Service factor	: 1.00
Breakdown torque	: 380 %	Temperature rise	: 80 K
Rated speed	: 1465 rpm	Design	: N

Locked rotor time : 16s (cold) 9s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 6 / 19	Revision
Checked by				
Date	24/10/2023			

# TORQUE AND CURRENT VS SPEED CURVE




## Three Phase Induction Motor - Squirrel Cage

Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code :

12867529



Performance : 460 V 60 Hz 4P

Rated current	: 12.7 A	Moment of inertia (J)	: 0.0563 kgm <sup>2</sup>
LRC	: 9.5	Duty cycle	: S1
Rated torque	: 4.13 kgfm	Insulation class	: F
Locked rotor torque	: 280 %	Service factor	: 1.00
Breakdown torque	: 400 %	Temperature rise	: 80 K
Rated speed	: 1770 rpm	Design	: N

Locked rotor time : 21s (cold) 12s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		7 / 19		
Date	24/10/2023			

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12867529



Performance : 380/660 V 50 Hz 4P

Rated current : 14.8/8.52 A  
 LRC : 8.3  
 Rated torque : 5.00 kgfm  
 Locked rotor torque : 220 %  
 Breakdown torque : 310 %  
 Rated speed : 1460 rpm

Moment of inertia (J) : 0.0563 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

# LOAD PERFORMANCE CURVE

## Three Phase Induction Motor - Squirrel Cage




Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code :

12867529



Performance : 400/690 V 50 Hz 4P

Rated current : 14.4/8.35 A  
 LRC : 8.5  
 Rated torque : 4.99 kgfm  
 Locked rotor torque : 240 %  
 Breakdown torque : 350 %  
 Rated speed : 1465 rpm

Moment of inertia (J) : 0.0563 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12867529



Performance : 415 V 50 Hz 4P

Rated current : 14.2 A  
 LRC : 8.7  
 Rated torque : 4.99 kgfm  
 Locked rotor torque : 260 %  
 Breakdown torque : 380 %  
 Rated speed : 1465 rpm

Moment of inertia (J) : 0.0563 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		10 / 19		
Date		24/10/2023		

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12867529



Performance : 460 V 60 Hz 4P

Rated current : 12.7 A  
 LRC : 9.5  
 Rated torque : 4.13 kgfm  
 Locked rotor torque : 280 %  
 Breakdown torque : 400 %  
 Rated speed : 1770 rpm

Moment of inertia (J) : 0.0563 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		11 / 19		
Date		24/10/2023		

# THERMAL LIMIT CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12867529



Performance : 380/660 V 50 Hz 4P

Rated current : 14.8/8.52 A  
 LRC : 8.3  
 Rated torque : 5.00 kgfm  
 Locked rotor torque : 220 %  
 Breakdown torque : 310 %  
 Rated speed : 1460 rpm

Moment of inertia (J) : 0.0563 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by	24/10/2023	Page		Revision
Checked by		12 / 19		
Date				

# THERMAL LIMIT CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12867529



Performance : 400/690 V 50 Hz 4P

Rated current : 14.4/8.35 A  
 LRC : 8.5  
 Rated torque : 4.99 kgfm  
 Locked rotor torque : 240 %  
 Breakdown torque : 350 %  
 Rated speed : 1465 rpm

Moment of inertia (J) : 0.0563 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date				
		Page	Revision	
		13 / 19		

# THERMAL LIMIT CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12867529



Performance : 415 V 50 Hz 4P

Rated current	: 14.2 A	Moment of inertia (J)	: 0.0563 kgm <sup>2</sup>
LRC	: 8.7	Duty cycle	: S1
Rated torque	: 4.99 kgfm	Insulation class	: F
Locked rotor torque	: 260 %	Service factor	: 1.00
Breakdown torque	: 380 %	Temperature rise	: 80 K
Rated speed	: 1465 rpm	Design	: N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 14 / 19	Revision
Checked by				
Date	24/10/2023			

# THERMAL LIMIT CURVE

## Three Phase Induction Motor - Squirrel Cage




Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code :

12867529



Performance : 460 V 60 Hz 4P

Rated current : 12.7 A  
 LRC : 9.5  
 Rated torque : 4.13 kgfm  
 Locked rotor torque : 280 %  
 Breakdown torque : 400 %  
 Rated speed : 1770 rpm


Moment of inertia (J) : 0.0563 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Heating constant  
 Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date				
		Page	Revision	
		15 / 19		

# VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12867529



Performance : 380/660 V 50 Hz 4P

Rated current : 14.8/8.52 A  
 LRC : 8.3  
 Rated torque : 5.00 kgfm  
 Locked rotor torque : 220 %  
 Breakdown torque : 310 %  
 Rated speed : 1460 rpm

Moment of inertia (J) : 0.0563 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

# VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12867529



Performance : 400/690 V 50 Hz 4P

Rated current : 14.4/8.35 A  
 LRC : 8.5  
 Rated torque : 4.99 kgfm  
 Locked rotor torque : 240 %  
 Breakdown torque : 350 %  
 Rated speed : 1465 rpm

Moment of inertia (J) : 0.0563 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

# VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12867529



Performance : 415 V 50 Hz 4P

Rated current	: 14.2 A	Moment of inertia (J)	: 0.0563 kgm <sup>2</sup>
LRC	: 8.7	Duty cycle	: S1
Rated torque	: 4.99 kgfm	Insulation class	: F
Locked rotor torque	: 260 %	Service factor	: 1.00
Breakdown torque	: 380 %	Temperature rise	: 80 K
Rated speed	: 1465 rpm	Design	: N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		18 / 19		
Date	24/10/2023			

# VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : W22 IE3 Three-Phase

Product code : 12867529



Performance : 460 V 60 Hz 4P

Rated current : 12.7 A  
 LRC : 9.5  
 Rated torque : 4.13 kgfm  
 Locked rotor torque : 280 %  
 Breakdown torque : 400 %  
 Rated speed : 1770 rpm

Moment of inertia (J) : 0.0563 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				