

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :						
Product line : IE3 Three-Phase	Product code : 12928519					
Frame : 90S/L Output : 1.1 kW (1.5 HP) Poles : 4 Frequency : 50 Hz Rated voltage : 230/400 V Rated current : 4.17/2.40 A L. R. Amperes : 31.7/18.2 A LRC : 7.6 No load current : 2.78/1.60 A Rated speed : 1455 rpm Slip : 3.00 % Rated torque : 0.736 kgfm Locked rotor torque : 250 % Breakdown torque : 330 % Insulation class : F Service factor : 1.00 Moment of inertia (J) : 0.0055 kgm ² Design : N	Locked rotor time : 27s (cold) 15s (hot) Temperature rise : 80 K Duty cycle : S1 Ambient temperature : -20°C to +40°C Altitude : 1000 m.a.s.l. Protection degree : IP55 Cooling method : IC411 - TEFC Mounting : B3T Rotation ¹ : Both (CW and CCW) Noise level ² : 49.0 dB(A) Starting method : Direct On Line Approx. weight ³ : 17.5 kg					
Output 50% 75% 100% Efficiency (%) 83.0 84.5 84.8 Power Factor 0.57 0.70 0.78	Foundation loads Max. traction : 59 kgf Max. compression : 76 kgf					
Losses at normative operating points (speed;torque), in percentage of rated output power						
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
17.5	15.6	14.7	9.2	6.9	5.2	3.9
		<u>Drive end</u>			<u>Non drive end</u>	
Bearing type	:	6205 ZZ			6204 ZZ	
Sealing	:	V'Ring			V'Ring	
Lubrication interval	:	-			-	
Lubricant amount	:	-			-	
Lubricant type	:	Mobil Polyrex EM				
Notes						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.		
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	24/10/2022				1 / 6	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	24/10/2022		2 / 6	

TORQUE AND CURRENT VS SPEED CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : IE3 Three-Phase

Product code : 12928519



Performance : 230/400 V 50 Hz 4P

Rated current	: 4.17/2.40 A	Moment of inertia (J)	: 0.0055 kgm ²
LRC	: 7.6	Duty cycle	: S1
Rated torque	: 0.736 kgfm	Insulation class	: F
Locked rotor torque	: 250 %	Service factor	: 1.00
Breakdown torque	: 330 %	Temperature rise	: 80 K
Rated speed	: 1455 rpm	Design	: N

Locked rotor time : 27s (cold) 15s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 3 / 6	Revision
Checked by				
Date	24/10/2022			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : IE3 Three-Phase

Product code : 12928519



Performance : 230/400 V 50 Hz 4P

Rated current : 4.17/2.40 A
 LRC : 7.6
 Rated torque : 0.736 kgfm
 Locked rotor torque : 250 %
 Breakdown torque : 330 %
 Rated speed : 1455 rpm

Moment of inertia (J) : 0.0055 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

THERMAL LIMIT CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : IE3 Three-Phase

Product code : 12928519



Performance : 230/400 V 50 Hz 4P

Rated current : 4.17/2.40 A
 LRC : 7.6
 Rated torque : 0.736 kgfm
 Locked rotor torque : 250 %
 Breakdown torque : 330 %
 Rated speed : 1455 rpm

Moment of inertia (J) : 0.0055 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : IE3 Three-Phase

Product code : 12928519



Performance : 230/400 V 50 Hz 4P

Rated current : 4.17/2.40 A
 LRC : 7.6
 Rated torque : 0.736 kgfm
 Locked rotor torque : 250 %
 Breakdown torque : 330 %
 Rated speed : 1455 rpm

Moment of inertia (J) : 0.0055 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 6 / 6	Revision
Checked by				
Date	24/10/2022			