

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer		: Astraprom d.o.o.			
Product line		: Multimounting IE3 Three-Phase		Product code : 13094940	
Frame	: 112M	Cooling method	: IC411 - TEFC		
Insulation class	: F	Mounting	: B5T		
Duty cycle	: S1	Rotation ¹	: Both (CW and CCW)		
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line		
Altitude	: 1000 m.a.s.l.	Approx. weight ²	: 37.8 kg		
Protection degree	: IP55	Moment of inertia (J)	: 0.0080 kgm ²		
Design	: N				
Output [kW]	4	4	4	4	4
Poles	2	2	2	2	2
Frequency [Hz]	50	50	50	50	60
Rated voltage [V]	380/660	400/690	415	460	460
Rated current [A]	7.84/4.51	7.62/4.42	7.52	6.67	6.67
L. R. Amperes [A]	58.0/33.4	58.7/34.0	60.2	57.4	57.4
LRC [A]	7.4	7.7	8.0	8.6	8.6
No load current [A]	2.80/1.61	3.10/1.80	3.30	2.90	2.90
Rated speed [RPM]	2890	2900	2910	3510	3510
Slip [%]	3.67	3.33	3.00	2.50	2.50
Rated torque [kgfm]	1.35	1.34	1.34	1.11	1.11
Locked rotor torque [%]	229	250	280	280	280
Breakdown torque [%]	310	350	380	440	440
Service factor	1.00	1.00	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	80 K
Locked rotor time	25s (cold) 14s (hot)	25s (cold) 14s (hot)	25s (cold) 14s (hot)	28s (cold) 16s (hot)	28s (cold) 16s (hot)
Noise level ²	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)	66.0 dB(A)	66.0 dB(A)
Efficiency (%)	25%				
	50%	87.0	86.5	86.0	85.5
	75%	87.5	87.5	87.0	87.5
	100%	88.1	88.1	88.1	88.5
Power Factor	25%				
	50%	0.73	0.69	0.65	0.67
	75%	0.83	0.80	0.77	0.79
	100%	0.88	0.86	0.84	0.85
Losses at normative operating points (speed;torque), in percentage of rated output power					
Losses (%)	P1 (0,9;1,0)	13.5	13.5	13.5	12.9
	P2 (0,5;1,0)	12.2	12.2	12.2	11.8
	P3 (0,25;1,0)	11.3	11.3	11.3	10.8
	P4 (0,9;0,5)	6.2	6.2	6.2	5.9
	P5 (0,5;0,5)	4.4	4.4	4.4	4.2
	P6 (0,5;0,25)	2.7	2.7	2.7	2.6
	P7 (0,25;0,25)	2.0	2.0	2.0	1.9
Bearing type	: Drive end 6207 ZZ	Non drive end 6206 ZZ	Foundation loads		
Sealing	: Oil Seal	Oil Seal	Max. traction	: 83 kgf	
Lubrication interval	: -	-	Max. compression	: 121 kgf	
Lubricant amount	: -	-			
Lubricant type	: Mobil Polyrex EM				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	11/01/2024			1 / 19	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Notes

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	11/01/2024		2 / 19	

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer : Astraprom d.o.o.

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by				Page 3 / 19
Checked by				
Date	11/01/2024			
				Revision

TORQUE AND CURRENT VS SPEED CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase

Product code : 13094940



Performance : 380/660 V 50 Hz 2P

Rated current	: 7.84/4.51 A	Moment of inertia (J)	: 0.0080 kgm ²
LRC	: 7.4	Duty cycle	: S1
Rated torque	: 1.35 kgfm	Insulation class	: F
Locked rotor torque	: 229 %	Service factor	: 1.00
Breakdown torque	: 310 %	Temperature rise	: 80 K
Rated speed	: 2890 rpm	Design	: N

Locked rotor time : 25s (cold) 14s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 4 / 19	Revision
Checked by				
Date	11/01/2024			

TORQUE AND CURRENT VS SPEED CURVE




Three Phase Induction Motor - Squirrel Cage

Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase

Product code : 13094940



Performance : 400/690 V 50 Hz 2P

Rated current : 7.62/4.42 A
 LRC : 7.7
 Rated torque : 1.34 kgfm
 Locked rotor torque : 250 %
 Breakdown torque : 350 %
 Rated speed : 2900 rpm

Moment of inertia (J) : 0.0080 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Locked rotor time : 25s (cold) 14s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		5 / 19		
Date	11/01/2024			

TORQUE AND CURRENT VS SPEED CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase

Product code : 13094940



Performance : 415 V 50 Hz 2P

Rated current	: 7.52 A	Moment of inertia (J)	: 0.0080 kgm ²
LRC	: 8.0	Duty cycle	: S1
Rated torque	: 1.34 kgfm	Insulation class	: F
Locked rotor torque	: 280 %	Service factor	: 1.00
Breakdown torque	: 380 %	Temperature rise	: 80 K
Rated speed	: 2910 rpm	Design	: N

Locked rotor time : 25s (cold) 14s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 6 / 19	Revision
Checked by				
Date	11/01/2024			

TORQUE AND CURRENT VS SPEED CURVE




Three Phase Induction Motor - Squirrel Cage

Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase

Product code :

13094940



Performance : 460 V 60 Hz 2P

Rated current	: 6.67 A	Moment of inertia (J)	: 0.0080 kgm ²
LRC	: 8.6	Duty cycle	: S1
Rated torque	: 1.11 kgfm	Insulation class	: F
Locked rotor torque	: 280 %	Service factor	: 1.00
Breakdown torque	: 440 %	Temperature rise	: 80 K
Rated speed	: 3510 rpm	Design	: N

Locked rotor time : 28s (cold) 16s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 7 / 19	Revision
Checked by				
Date	11/01/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase

Product code : 13094940



Performance : 380/660 V 50 Hz 2P

Rated current : 7.84/4.51 A
 LRC : 7.4
 Rated torque : 1.35 kgfm
 Locked rotor torque : 229 %
 Breakdown torque : 310 %
 Rated speed : 2890 rpm

Moment of inertia (J) : 0.0080 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 8 / 19	Revision
Checked by				
Date	11/01/2024			

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase

Product code :

13094940



Performance : 400/690 V 50 Hz 2P

Rated current : 7.62/4.42 A
 LRC : 7.7
 Rated torque : 1.34 kgfm
 Locked rotor torque : 250 %
 Breakdown torque : 350 %
 Rated speed : 2900 rpm

Moment of inertia (J) : 0.0080 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase

Product code : 13094940



Performance : 415 V 50 Hz 2P

Rated current : 7.52 A
 LRC : 8.0
 Rated torque : 1.34 kgfm
 Locked rotor torque : 280 %
 Breakdown torque : 380 %
 Rated speed : 2910 rpm

Moment of inertia (J) : 0.0080 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 10 / 19	Revision
Checked by				
Date	11/01/2024			

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase

Product code :

13094940



Performance : 460 V 60 Hz 2P

Rated current : 6.67 A
 LRC : 8.6
 Rated torque : 1.11 kgfm
 Locked rotor torque : 280 %
 Breakdown torque : 440 %
 Rated speed : 3510 rpm

Moment of inertia (J) : 0.0080 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				
			11 / 19	

THERMAL LIMIT CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase

Product code : 13094940



Performance : 380/660 V 50 Hz 2P

Rated current : 7.84/4.51 A
 LRC : 7.4
 Rated torque : 1.35 kgfm
 Locked rotor torque : 229 %
 Breakdown torque : 310 %
 Rated speed : 2890 rpm

Moment of inertia (J) : 0.0080 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by	11/01/2024	Page 12 / 19		Revision
Checked by				
Date				

THERMAL LIMIT CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase

Product code : 13094940



Performance : 400/690 V 50 Hz 2P

Rated current : 7.62/4.42 A
 LRC : 7.7
 Rated torque : 1.34 kgfm
 Locked rotor torque : 250 %
 Breakdown torque : 350 %
 Rated speed : 2900 rpm

Moment of inertia (J) : 0.0080 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date				
		Page	Revision	
		13 / 19		

THERMAL LIMIT CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase

Product code : 13094940



Performance : 415 V 50 Hz 2P

Rated current	: 7.52 A	Moment of inertia (J)	: 0.0080 kgm ²
LRC	: 8.0	Duty cycle	: S1
Rated torque	: 1.34 kgfm	Insulation class	: F
Locked rotor torque	: 280 %	Service factor	: 1.00
Breakdown torque	: 380 %	Temperature rise	: 80 K
Rated speed	: 2910 rpm	Design	: N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 14 / 19	Revision
Checked by				
Date	11/01/2024			

THERMAL LIMIT CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase

Product code : 13094940



Performance : 460 V 60 Hz 2P

Rated current	: 6.67 A	Moment of inertia (J)	: 0.0080 kgm ²
LRC	: 8.6	Duty cycle	: S1
Rated torque	: 1.11 kgfm	Insulation class	: F
Locked rotor torque	: 280 %	Service factor	: 1.00
Breakdown torque	: 440 %	Temperature rise	: 80 K
Rated speed	: 3510 rpm	Design	: N

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date	11/01/2024			

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase

Product code : 13094940



Performance : 380/660 V 50 Hz 2P

Rated current : 7.84/4.51 A
 LRC : 7.4
 Rated torque : 1.35 kgfm
 Locked rotor torque : 229 %
 Breakdown torque : 310 %
 Rated speed : 2890 rpm

Moment of inertia (J) : 0.0080 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 16 / 19	Revision
Checked by				
Date	11/01/2024			

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase

Product code : 13094940



Performance : 400/690 V 50 Hz 2P


Rated current : 7.62/4.42 A
 LRC : 7.7
 Rated torque : 1.34 kgfm
 Locked rotor torque : 250 %
 Breakdown torque : 350 %
 Rated speed : 2900 rpm

Moment of inertia (J) : 0.0080 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 17 / 19	Revision
Checked by				
Date	11/01/2024			

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase

Product code : 13094940



Performance : 415 V 50 Hz 2P

Rated current	: 7.52 A	Moment of inertia (J)	: 0.0080 kgm ²
LRC	: 8.0	Duty cycle	: S1
Rated torque	: 1.34 kgfm	Insulation class	: F
Locked rotor torque	: 280 %	Service factor	: 1.00
Breakdown torque	: 380 %	Temperature rise	: 80 K
Rated speed	: 2910 rpm	Design	: N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : Astraprom d.o.o.

Product line : Multimounting IE3 Three-Phase

Product code : 13094940



Performance : 460 V 60 Hz 2P

Rated current : 6.67 A
 LRC : 8.6
 Rated torque : 1.11 kgfm
 Locked rotor torque : 280 %
 Breakdown torque : 440 %
 Rated speed : 3510 rpm

Moment of inertia (J) : 0.0080 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		19 / 19		
Date		11/01/2024		