


## KRV32-PP

### Yoke type track roller

Schaeffler ID:  
0055917910000

Stud type track rollers KRV...-PP, with axial guidance, full complement needle roller set, plastic axial plain washers on both sides

## Technical information



### Main Dimensions & Performance Data

D	32 mm	Outside diameter
d <sub>1</sub>	12 mm	Fit diameter of roller stud / stud
B	40 mm	Width
C <sub>r w</sub>	10.000 N	Basic dynamic load rating, radial
C <sub>0r w</sub>	16.300 N	Basic static load rating, radial
C <sub>ur w</sub>	2.240 N	Fatigue load limit, radial
n <sub>D G</sub>	2.100 1/min	Speed on permanent grease lubrication
≈m	111 g	Weight

### Dimensions

B <sub>1</sub>	15,2 mm	Width of thrust washer
B <sub>2</sub>	25 mm	Bolt/stud length effectively
B <sub>3</sub>	6 mm	Distance to lubrication hole
C	14 mm	Width, outer ring
C <sub>1</sub>	0,6 mm	Protrusion outer ring to thrust washer
r <sub>min</sub>	0,6 mm	Minimum chamfer dimension
d <sub>2</sub>	23 mm	Stop diameter of thrust washer
d <sub>3</sub>	3 mm	Diameter lubrication hole
G	M12X1,5	Thread
l <sub>G</sub>	13 mm	Thread length
W	6 mm	Width of flats

### Additional information

	NIPA1X4,5	Drive-fit lubrication nipple
M <sub>A</sub>	22 Nm	Tightening torque nut