



FAG

## NJ2222-E-XL-M1




Cylindrical roller bearing

Schaeffler ID:  
0192239190000

Cylindrical roller bearing NJ..-E-XL-M1, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

## Technical information



## Main Dimensions &amp; Performance Data

d	110 mm	Bore diameter
D	200 mm	Outside diameter
B	53 mm	Width
$C_r$	455.000 N	Basic dynamic load rating, radial
$C_{0r}$	520.000 N	Basic static load rating, radial
$C_{ur}$	88.000 N	Fatigue load limit, radial
$n_G$	6.100 1/min	Limiting speed
$n_{gr}$	2.750 1/min	Reference speed
	7,6 kg	Weight

## Dimensions

$d_{a \min}$	122 mm	Minimum diameter shaft shoulder
$r_{\min}$	2,1 mm	Minimum chamfer dimension
$d_{a \max}$	130 mm	Maximum diameter of shaft shoulder
$r_{1 \min}$	2,1 mm	Minimum chamfer dimension
s	3,9 mm	Axial displacement
$D_{a \max}$	188 mm	Maximum diameter of housing shoulder
E	180,5 mm	Raceway diameter outer ring
F	132,5 mm	Raceway diameter inner ring
$D_{1 \min}$	173,82 mm	Minimum rib diameter outer ring
$d_{c \min}$	144 mm	Minimum shaft shoulder
$d_1$	141,55 mm	Maximum rib diameter inner ring
$r_{a \max}$	2 mm	Maximum recess radius

## Additional information

HJ2222-E	L-washer
----------	----------

## Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

